

Klübersynth CTH 2-260

High-temperature oil for oil-lubricated stenter chains in the textile industry



Your benefits at a glance

- **Effective lubrication at high operating temperatures**
- **No varnish build-up**
- **Low evaporation loss at high temperatures**
- **Regenerates pasty used oil at the lubrication points for improved lubrication**
- **Good compatibility with non-ferrous metals**
- **Very good spreading and wetting ability, also in chains with plastic sprags**

Your requirements – our solution

The textile industry is demanding high-temperature chain oils offering ever higher thermal stability and longer relubrication intervals.

With these requirements in mind, we developed our synthetic high-temperature chain oil Klübersynth CTH 2-260.

Klübersynth CTH 2-260 is a special high-temperature chain oil for reliable lubrication at high operating temperatures and loads. Klübersynth CTH 2-260 has low evaporation losses at high temperatures and does not form varnish build-up when used correctly - it is important to keep friction points covered with an oil film at all times. Klübersynth CTH 2-260 also regenerates pasty used oil at the friction points to ensure sufficient lubrication. It also offers good creeping ability, ensuring quick lubricant film formation.

Due to the low evaporation losses and the good antiwear effect, Klübersynth CTH 2-260 enables longer relubrication intervals and consequently lower operating costs.

Findings about Klübersynth CTH 2-260 obtained in tests and field use:

- High viscosity index for easy cold starting of your machine, reducing power input with better viscosity-temperature behaviour.
- Improved penetration and better wetting of the lubrication and friction points, in particular the chain links.
- Good adhesion and sufficient carry-over in long machines.
- Less oil residue for reduced chain contamination and extended chain cleaning intervals if applied evenly and appropriately dosed.
- Prevents adhesion of most condensates on the friction points.
- Effective lubrication also at high operating temperatures.
- No varnish build-up with total loss lubrication.
- Low evaporation rate at high temperatures

- Regenerates pasty used oil at the lubrication and friction points for improved lubrication.
- Good compatibility with non-ferrous metals.
- Good spreading and wetting ability in chains with plastic sprags.

Application

With Klübersynth CTH 2-260, the range of Klüber Lubrication high-temperature chain oils has been consistently upgraded. The product can replace other Klüber Lubrication chain oils for high operating temperatures.

It can be used for all types of oil-lubricated stenter chains, e.g.

- roller chains
- chains or clips with ball bearings - combined lubrication of ball bearings, chain links and sliding rails
- sliding chains in single-layer stenters, multi-layer stenters, festoon dryers, festoon steamers, coating installations - lubrication of sliding rails, chain links and chain pins

Application notes

Klübersynth CTH 2-260 can normally be used to replace other Klüber Lubrication chain oils without specific preparations. It is miscible and compatible with our chain oils so under normal operating conditions the chain system does not require prior cleaning. Oil reservoirs, however, should be completely drained prior to filling them with Klübersynth CTH 2-260.

Klübersynth CTH 2-260 can be applied by means of customary pumping, spraying and metering equipment provided the manufacturers' viscosity instructions are observed. Lubrication intervals and quantities are determined by the chain design, lubrication technique and the variable operating conditions. At operating temperatures > 180 °C, chain oil consumption in stenter chains will be at approx. 1.5 to 2 ml of oil per chain

Klübersynth CTH 2-260

High-temperature oil for oil-lubricated stenter chains in the textile industry

metre and shift. Chain sliding rails should be lubricated continuously or at short intervals, taking into account the chain design and length.

Long lubrication intervals tend to heighten the risk of wear damage due to lubricant starvation. It is better to apply precisely metered lubricant quantities at regular intervals, i.e. at least once per day or shift. Over-lubrication should be avoided as splashing oil might contaminate the fabric.

Note:

According to our experience from bench tests and field use, Klübersynth CTH 2-260 does not form varnish build-up, provided that it is applied properly, i.e. chains and sliding rails should be covered with an oil film at all times. Powdered residues may only occur after evaporation of the volatile

constituents in the event of excessive thermal stress combined with untimely relubrication. Feeding fresh oil at the right time helps regenerate the residues, ensuring proper supply of the lubrication points with chain oil.

To optimise the service life of your equipment or if you have any other questions regarding your application, our experts will be pleased to help you. We look forward to hearing from you.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	Klübersynth CTH 2-260
Canister 5 l	+
Canister 20 l	+
Drum 200 l	+

Product data	Klübersynth CTH 2-260
Article number	002108
Upper service temperature	250 °C / 482 °F
Colour space	yellow
Appearance	clear
Density, DIN 51757, 20 °C	approx. 0.92 g/cm ³
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 20 °C	approx. 800 mm ² /s
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C	approx. 260 mm ² /s
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 100 °C	approx. 30 mm ² /s
Viscosity index, DIN ISO 2909	>= 135
Flash point, DIN EN ISO 2592, Cleveland, open-cup apparatus	>= 260 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	24 months





Klübersynth CTH 2-260

High-temperature oil for oil-lubricated stenter chains in the textile industry



Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

**Klüber Lubrication München SE & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.**

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.