

Klübersynth NH1 4-68 Foam Spray

Highly adhesive oil based on an innovative foam technology



Benefits for your application

- NSF H1-registered product suitable for use in the food-processing industry
- Excellent adhesiveness ensures good lubrication effect and reduced wear
- Unique foam combination with oil supports easy application including overhead application without dripping
- Optimised consumption due to capillary action, ensuring slow but clear penetration of the lubricant to the friction point

Description

Klübersynth NH1 4-68 Foam Spray is a synthetic oil-based multifunctional fluid spray. The excellent adhesiveness of the foam holds the lubricant at the friction point to reduce wear.

The combination of foam and oil that Klübersynth NH1 4-68 Foam Spray offers ensures that the oil reaches the exact lubrication point due to capillary action. This combination also ensures that the dripping problem noticed with conventional oil is clearly reduced.

The combination of foam and oil reduces overspray and thus mist formation as with conventional sprays. This avoids unwanted contamination of surrounding components and surfaces. Additionally, possible inhalation risks of oil mist are eliminated.

In spite of the oil having a low viscosity, it still exhibits good lubrication and wear protection properties.

- Ideal product for maintenance personal tool kit

Application notes

Klübersynth NH1 4 -68 Foam Spray can be directly applied to lubrication points. However, we would recommend to clean the lubrication points in order to maximise the effect of lubricant performance.

Shake well before use.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Application

- Klübersynth NH1 4 -68 Foam Spray is suitable for the lubrication of spindles, open gears, hinges, sliding rails and for chains (3-5 m)

Pack sizes	Klübersynth NH1 4-68 Foam-Spray
Aerosol can 225 ml	+

Product data	Klübersynth NH1 4-68 Foam-Spray
Article number	081332
NSF-H1 registration	148 259
Lower service temperature	-35 °C / -31 °F
Upper service temperature	120 °C / 248 °F
Colour space	colourless
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C	approx. 68 mm ² /s



Klübersynth NH1 4-68 Foam Spray

Highly adhesive oil based on an innovative foam technology

Product data	Klübersynth NH1 4-68 Foam-Spray
ISO viscosity grade, DIN ISO 3448	68
Anticorrosive properties on steel, DIN ISO 7120, method A, steel, 24 h/60 °C	no rust corrosion degree
Copper corrosion, DIN EN ISO 2160, 24 h/100°C	1 - 100 corrosion degree
Pour point, DIN ISO 3016	<= -36 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	24 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

**Klüber Lubrication München SE & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.**

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.