



# MOTOR DATA SHEET

**MOTOR PART CODE:**

**0.2543TECAB3**

**FRAME SIZE:**

**711-4**

**50Hz**

Output (kW)	0.25
Rotation Speed (rpm)	1350
Voltage	230/400
Full Load Current (A)	1.45   0.84
Full Load Torque (Nm)	1.768518519

**60Hz**

Output (kW)	0.3
Rotation Speed (rpm)	1620
Voltage	276   480
Full Load Current (A)	1.45   0.84
Full Load Torque (Nm)	1.47

## Efficiency Data

100%	75%	50%
60	59	56

Factory Reference	MS711-4
Tst/Tn (times)	2.2
Tmax/Tn	2.4
Noise (dB)	55
Moment of inertia	0.000560559
Type of feet	Removable feet
Protection	IP55
Rotation Direction	F / R
Cable Glands	1 - M20× 1.5
Paint Colour	RAL 7024
Efficiency	IE1
Bearing (DE)	6202 2RS C3

Power Factor (cos)	0.72
Tmin/Tn	1.7
Ist/In (Times)	6
Net Weight (Kg)	5
Housing material	Aluminum
Insulation Class	F
Thermal Protection	PTC 130°C
Duty Cycle	S1
Cooling	IC411
Ambient Temperature	-20°C to +40°
Bearing Brand	NSK
Bearing (NDE)	6202 2RS C3

*Motors designed and manufactured in accordance with:*

**IEC 60034  
IEC 60038  
IEC 60072  
2014/30/EU (EMC)  
2014/35/EU (LVD)  
2011/65/EU (RoHS 2)**

[www.tecmotors.co.uk](http://www.tecmotors.co.uk)

TEC Electric Motors Ltd. reserves the right to amend or change motor designs or data sheet information