



# MOTOR DATA SHEET

**MOTOR PART CODE:**

**15.023TECCB3-IE2**

**FRAME SIZE:**

**160M2-2**

	<b>50Hz</b>
Output (kW)	15
Rotation Speed (rpm)	2940
Voltage	400/690
Full Load Current (A)	26.64/15.38
Full Load Torque (Nm)	48.72

	<b>60Hz</b>
Output (kW)	18
Rotation Speed (rpm)	3528
Voltage	480/828
Full Load Current (A)	26.64/15.38
Full Load Torque (Nm)	40.60

## Efficiency Data

<b>100%</b>	<b>75%</b>	<b>50%</b>
90.3	90	88.8

Factory Reference	T2C 160M2-2
Tst/Tn (times)	2.5
Tmax/Tn	2.8
Noise (dB)	86
Moment of inertia	0.06206
Type of feet	Removable feet
Protection	IP55
Rotation Direction	F / R
Cable Glands	2 - M32× 1.5
Paint Colour	RAL 7024
Efficiency	IE2
Bearing (DE)	6309 C3

Power Factor (cos)	0.9
Tmin/Tn	1.3
Ist/In (Times)	9
Net Weight (Kg)	124
Housing material	Cast Iron
Insulation Class	F
Thermal Protection	PTC 140°C
Duty Cycle	S1
Cooling	IC 411
Ambient Temperature	-20°C to +40°C
Bearing Brand	NSK
Bearing (NDE)	6309 C3

*Motors designed and manufactured in accordance with:*

**IEC 60034  
IEC 60038  
IEC 60072  
2014/30/EU (EMC)  
2014/35/EU (LVD)  
2011/65/EU (RoHS 2)**

[www.tecmotors.co.uk](http://www.tecmotors.co.uk)

TEC Electric Motors Ltd. reserves the right to amend or change motor designs or data sheet information