



MOTOR DATA SHEET

MOTOR PART CODE:

30.023TECAB3-IE2

FRAME SIZE:

200L1-2

| | 50Hz |
|-----------------------|---------------|
| Output (kW) | 30 |
| Rotation Speed (rpm) | 2950 |
| Voltage | 400/690 |
| Full Load Current (A) | 51.72 29.86 |
| Full Load Torque (Nm) | 97.11864407 |

| | 60Hz |
|-----------------------|---------------|
| Output (kW) | 36 |
| Rotation Speed (rpm) | 3540 |
| Voltage | 480 828 |
| Full Load Current (A) | 51.72 29.86 |
| Full Load Torque (Nm) | 80.93 |

Efficiency Data

| 100% | 75% | 50% |
|------|------|------|
| 92 | 91.4 | 89.3 |

| | |
|--------------------|----------------|
| Factory Reference | MS2 200L1-2 |
| Tst/Tn (times) | 2.5 |
| Tmax/Tn | 3.3 |
| Noise (dB) | 94 |
| Moment of inertia | 0.1222455 |
| Type of feet | Removable feet |
| Protection | IP55 |
| Rotation Direction | F / R |
| Cable Glands | 2 - M40× 1.5 |
| Paint Colour | RAL 7024 |
| Efficiency | IE2 |
| Bearing (DE) | 6312 2RS C3 |

| | |
|---------------------|-----------------|
| Power Factor (cos) | 0.91 |
| Tmin/Tn | 1.3 |
| Ist/In (Times) | 8.8 |
| Net Weight (Kg) | 158 |
| Housing material | Aluminum |
| Insulation Class | F |
| Thermal Protection | PTC 130°C |
| Duty Cycle | S1 |
| Cooling | IC411 |
| Ambient Temperature | -20°C to + 40°C |
| Bearing Brand | NSK |
| Bearing (NDE) | 6212 2RS C3 |

Motors designed and manufactured in accordance with:

**IEC 60034
IEC 60038
IEC 60072
2014/30/EU (EMC)
2014/35/EU (LVD)
2011/65/EU (RoHS 2)**

www.tecmotors.co.uk

TEC Electric Motors Ltd. reserves the right to amend or change motor designs or data sheet information