



MOTOR DATA SHEET

MOTOR PART CODE:

75.043TECCB3-IE2

FRAME SIZE:

280S-4

	50Hz
Output (kW)	75
Rotation Speed (rpm)	1480
Voltage	400/690
Full Load Current (A)	127.96/73.87
Full Load Torque (Nm)	484

	60Hz
Output (kW)	90
Rotation Speed (rpm)	1776
Voltage	480/828
Full Load Current (A)	127.96/73.87
Full Load Torque (Nm)	403.33

Efficiency Data

100%	75%	50%
94	94.9	93.7

Factory Reference	T2C 280S-4
Tst/Tn (times)	2.5
Tmax/Tn	2.5
Noise (dB)	86
Moment of inertia	1.5951
Type of feet	Removable feet
Protection	IP55
Rotation Direction	F / R
Cable Glands	2 - M50× 1.5
Paint Colour	RAL 7024
Efficiency	IE2
Bearing (DE)	6316 C3

Power Factor (cos)	0.9
Tmin/Tn	2
Ist/In (Times)	9
Net Weight (Kg)	580
Housing material	Cast Iron
Insulation Class	F
Thermal Protection	PTC 140°C
Duty Cycle	S1
Cooling	IC 411
Ambient Temperature	-20°C to +40°C
Bearing Brand	NSK
Bearing (NDE)	6316 C3

Motors designed and manufactured in accordance with:

**IEC 60034
IEC 60038
IEC 60072
2014/30/EU (EMC)
2014/35/EU (LVD)
2011/65/EU (RoHS 2)**

www.tecmotors.co.uk

TEC Electric Motors Ltd. reserves the right to amend or change motor designs or data sheet information