

AC140 Series



Low Cost Miniature Industrial Multipurpose Accelerometer, Top Exit
2 Pin Mini-MIL Connector, 100 mV/g, ±15%

VIBRATION ANALYSIS HARDWARE



Product Features


Mini Industrial Accelerometer, Great for Hard-to-Reach Locations

- ▶ Mini, Easy to Manage Size
- ▶ 2 Pin Mini-MIL Connection
- ▶ ±15% Sensitivity

AC140-1D

2 Pin Mini Mil Connector

Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common



Stock Product

AC140-2D

CB110 Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC140-3D

CB206 Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC140-6D

CB611 Heavy Duty Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC140-6N

CB111 Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC140	M/AC140	Environmental		
Sensitivity (±15%)		100 mV/g	Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response (±3dB)	36-900,000 CPM	0.6-15000 Hz	Maximum Shock Protection		5,000 g, peak
Frequency Response (±10%)	60-420,000 CPM	1.0-7000 Hz	Electromagnetic Sensitivity		CE
Dynamic Range		± 50 g, peak	Sealing		Welded, Hermetic
Electrical			Submersible Depth	200 ft.	60 m
Settling Time		<2.5 seconds	Physical		
Voltage Source (IEPE)		18-30 VDC	Sensing Element		PZT Ceramic
Constant Current Excitation		2-10 mA	Sensing Structure		Shear Mode
Spectral Noise @ 10 Hz		30 µg/√Hz	Weight	0.7 oz	20 grams
Spectral Noise @ 100 Hz		4 µg/√Hz	Case Material		316L Stainless Steel
Spectral Noise @ 1000 Hz		2 µg/√Hz	Mounting		1/4-28
Output Impedance		<100 ohm	Connector (Non-Integral)		2 Pin mini-MIL (J Series)
Bias Output Voltage		10-14 VDC	Resonant Frequency	2,040,000 CPM	34000 Hz
Case Isolation		>10 ⁸ ohm	Mounting Torque	2 to 5 ft. lbs.	2.7 to 6.8 Nm
			Mounting Hardware	1/4-28 Stud	M6x1 Adapter Stud
			Calibration Certificate		CA10

Typical Frequency Response



Backed by our Unconditional Lifetime Warranty

www.ctconline.com | sales@ctconline.com | 585-924-5900